

Claims

What is claimed is:

1. A shaving system, comprising:

- a) a pivot frame;
- b) a pivot assembly pivotally coupled to said pivot frame; and
- c) a blade assembly pivotally coupled to said pivot assembly.

2. A shaving system according to claim 1, wherein said blade assembly is rotatable relative to said pivot assembly from a first position to a second position and when in said first position, rotation of said pivot assembly relative to said pivot frame causes rotation of said blade assembly about a center axis of said blade assembly.

3. A shaving system according to claim 2, wherein for said blade assembly is rotatable relative to said pivot assembly from a first position to a second position and when in said second position, rotation of said pivot assembly relative to said pivot frame causes rotation of said blade assembly about a guard-bar axis of said blade assembly.

4. A shaving system according to claim 1, further comprising:
d) first biasing means between said blade assembly and said pivot assembly; and
e) second biasing means between said pivot assembly and said pivot frame.

5. A shaving system according to claim 4, wherein said first biasing means is stronger than said second biasing means.

6. A shaving system according to claim 4, wherein said second biasing means allows bi-directional rotation of said pivot assembly relative to said pivot frame.

7. A shaving system according to claim 4, wherein said second biasing means allows only uni-directional rotation of said pivot assembly relative to said pivot frame.

5 8. A shaving system according to claim 4, wherein said second biasing means is a cantilevered spring.

9. A shaving system according to claim 4, wherein said second biasing member is a cam follower.

10

10. A shaving system according to claim 1, wherein said blade assembly is rotatable approximately 45° relative to said pivot assembly.

11. A shaving system according to claim 10, wherein said pivot assembly is rotatable approximately $\pm 20^\circ$ relative to said pivot frame.

15

12. A shaving system according to claim 10, wherein said pivot assembly is rotatable approximately 40° relative to said pivot frame.

20

13. A shaving system, comprising:
- a) a shaving cartridge that rotates relative to a pivot;
 - b) a pivot that rotates relative to a pivot frame; and
 - c) a pivot frame.

25

14. A shaving system as set forth in claim 13, wherein said shaving cartridge rotates relative to a pivot going from a center pivot to a guard-bar pivot.

15. A shaving system as set forth in claim 13, wherein said shaving cartridge rotates relative to a pivot going from a center pivot substantially on said shave plane to a guard-bar pivot substantially on said shave plane.

30

16. A shaving system as set forth in claim 13, wherein said shaving cartridge rotates relative to a pivot going from a center pivot substantially on said

shave plane to a guard-bar pivot substantially on said shave plane as loading increases.

17. A shaving system as set forth in claim 16, wherein said shaving
5 cartridge rotates relative to said pivot going back from a guard-bar pivot substantially on said shave plane to a center pivot substantially on said shave plane as loading decreases.

18. A shaving system as set forth in claim 17, wherein said pivot relative
10 to said pivot frame supports unidirectional pivoting.

19. A shaving system as set forth in claim 17, wherein said pivot relative
to said pivot frame supports bi-directional pivoting.

20. A triple blade shaving system, comprising:
15 a) a pivot frame;
b) a pivot assembly pivotally coupled to said pivot frame; and
c) a triple blade, blade assembly pivotally coupled to said pivot
assembly,

wherein said blade assembly is rotatable relative to said pivot assembly from a first
20 position to a second position; and (1) when in said first position, rotation of said pivot
assembly relative to said pivot frame causes rotation of said blade assembly about a
center axis, substantially on the shave plane, of said blade assembly; and (2) when in
said second position, rotation of said pivot assembly relative to said pivot frame
causes rotation of said blade assembly, substantially on said shave plane, about a
25 guard-bar axis of said blade assembly.